





Features

The lean machine, Rubber mounted tacho and speedo binnacle with ignition/oil. neutral gear, direction indicator, and high beam warning lights.

Rear brake caliper now carried above rear wheel centre, a position clear of water spray improving operation under adverse conditions.

America's famous cast alloy wheel—the Lester as fitted to the Bonneville 'Special' Lighter stronger easy to clean.

The American 2 gallon tank, traditional Triumph. Available in a range of striking colour schemes.


Specifically designed and developed for Triumph, the electronic ignition system ensures 100% accurate timing and no adjustments or maintenance.

Brake fluid reservoir now positioned inside RH side panel with access through window, secure from dirt and damage.

The world famous Triumph Twin engine with forty years of road and track development behind it. Twin cylinders with alloy head, two gear driven camshafts, alloy connecting rods and plain big-ends. Massive crankshaft with end mounted alternator, 12v electrics, electronic ignition, Amal carburetters. 5 speed unit gearbox.

The European 4 gallon tank, stylish, colourful and providing adequate fuel supply for the long distance rider.

The Bonneville 'Special' with the new custom contoured twin level seat sets a high standard in comfort and ease of riding, plus a two-into-one exhaust giving that lean look with increased clearance for cornering.



Technical Data

9 Engine Type Bore Stroke Capacity Compression Ratio Gearing: **Engine Sprocket** Clutch Sprocket Gearbox Sprocket Rear Wheel Sprocket 8 Carburettors Primary Chain Rear Chain Rear Tyre

Front Tyre Front Brake Rear Brake Gearbox type Gear ratio, 1st Gear ratio, 2nd Gear ratio, 3rd Gear ratio, 4th Gear ratio.5th Top gear rpm at 10mph Wheelbase Length, Overall Width

Seat height Ground clearance Dry weight Fuel capacity Fuel capacity

U.S. version (Bonneville only) Oil capacity Electrical System Ignition System

T140E TR7V T140D

OHV. parallel twin, four stroke 76mm (2.992 in) 82mm (3.228in) 744cc (45c.in) 7.9:1

58 teeth 20 teeth 47 teeth

Twin Amal MkII (Single Amal 930 TR7V) % in Triplex Renold

%×% in Renold 4.10×19

29 teeth

 $4.10 \times 18 (4.25 \times 18 \text{ T} 140 \text{D})$ 10 in (254mm) disc

10in (254mm) disc five-speed

12.14 8.63 6.58 5.59 4.70 625

56 in (1420mm) 87½ in (2220mm) 27in (736mm) 31in (790mm) 7in (180mm) 413lb (187kg) 4 Imp. gal (18.2 litres)

2 Imp. gal (9.1 litres) 5 Imp. pints (2.8 litres) 12 volts, 3-phase alternator Lucas Electronic

Triumph Motorcycles (Meriden) Limited including all associated companies reserve the right to vary the specification of all motorcycles and spare parts without notice and the information in this leaflet does not therefore constitute a term of any sale. All descriptions and claims are given and made in good faith but are intended to apply generally. Variations in performance and construction on individual machines may occur. Performance on any particular occasion will also be affected by the conditions, circumstances and the rider.